

## KCB3E3E3E3E0000DV0W (Order no. 083331)

### Series KC...

- ▶ Screw terminal
- ▶ 4 actuating directions
- ▶ Pushbutton in handle (D)
- ▶ Interlocking in switch position 0 (V0)
- ▶ Bellows for panel mounting (W)



## Technical data

### Approvals



### Electrical connection values

Fuse	T6/F10
Rated insulation voltage $U_i$	250 V
Rated impulse voltage $U_{imp}$	2.5 kV
Utilization category	
	DC-13 24V 2A
	AC-15 230V 4A
Switching voltage	min. 10 V
Switching current	
	(at 24V) min. 12 mA

### Pushbutton in handle

Utilization category	
	AC-15 230V 2A
	DC-13 24V 1A
Switching voltage	min. 10 V
Switching current	
	(at 24V) min. 12 mA

### Mechanical values and environment

Connection type	Screw terminal
Number of monitoring contacts	max. 4 4 (4 directions x 1 switching element)
Actuating directions	max. 4 max. 3 positions (0-1-2) possible per type and direction
Storage temperature	-25 ... 70 °C
Mechanical life	1 x 10 <sup>6</sup>
Mounting cut-out	Ø 52 mm

Switching principle	Changeover contact C, IEC 947-5-1 (Snap-action contact element, design ES556)
---------------------	--

Degree of protection

on the front with bellows IP65  
(Version W)

Ambient temperature	-5 ... 65 °C
---------------------	--------------

Material

Switching lever galvanized steel  
Contact Silver alloy  
Bellows elastomer, black  
(Low PAH)  
Housing thermoplastic/aluminum

## Pushbutton in handle

Actuating force max. 8 N

Mechanical life

(at 0.7A / 250V AC) 0.05 x 10<sup>6</sup>

Switching principle 1 contact

## Miscellaneous

Additional feature

Pushbutton in handle  
Interlocking in center position  
Bellows W for panel mounting