

WES13W (Order no. 045350)

Series WE...

- ▶ Control panel installation at rear or with front plate
- ▶ Switch with actuating directions 1+3
- ▶ One changeover contact with screw terminal for each actuating direction
- ▶ Bellows



Technical data

Approvals



Electrical connection values

Fuse	T16/F25
Rated insulation voltage U_i	250 V
Rated impulse voltage U_{imp}	2.5 kV
Utilization category	
	AC-15 230V 10A
	DC-13 24V 4A
Switching voltage	min. 24 V
Switching current	
	(at 24V) min. 50 mA

Mechanical values and environment

Connection type	Screw terminal
Number of monitoring contacts	2 (2 directions)
Actuating directions	2 (Switch)
Storage temperature	-25 ... 70 °C
Mechanical life	1 x 10 ⁶
Mounting cut-out	Ø 42 mm
Switching principle	Changeover contact ZA, IEC 947-5-1 (Snap-action contact element, design ES502V1)
Degree of protection	
	on the front with bellows IP65
Ambient temperature	-25 ... 65 °C

Material

- Contact Silver alloy
- Bellows elastomer, black
- (Low PAH)
- Housing thermoplastic/aluminum
- Switching lever galvanized steel

Miscellaneous

Additional feature	Bellows
--------------------	---------