

WET1234FW (Order no. 018602)

Series WE...

- ▶ Control panel installation at rear or with front plate
- ▶ Pushbutton with actuating directions 1-4
- ▶ One changeover contact with screw terminal for each actuating direction
- ▶ Front panel
- ▶ Bellows



Technical data

Approvals



Electrical connection values

Fuse	T16/F25
Rated insulation voltage U_i	250 V
Rated impulse voltage U_{imp}	2.5 kV
Utilization category	AC-15 230V 10A DC-13 24V 4A
Switching voltage	min. 24 V
Switching current	(at 24V) min. 50 mA

Mechanical values and environment

Connection type	Screw terminal
Number of monitoring contacts	4 (4 directions)
Actuating directions	4 (Pushbutton)
Storage temperature	-25 ... 70 °C
Mechanical life	1 x 10 ⁶
Mounting cut-out	Ø 42 mm
Switching principle	Changeover contact ZA, IEC 947-5-1 (Snap-action contact element, design ES502V1)
Degree of protection	on the front with bellows IP65
Ambient temperature	-5 ... 65 °C

Material

Switching lever galvanized steel

Housing thermoplastic/aluminum

Bellows elastomer, black

(Low PAH)

Contact Silver alloy

Miscellaneous

Additional feature

Bellows

Front panel