

## WES1234W (Order no. 018632)

### Series WE...

- ▶ Control panel installation at rear or with front plate
- ▶ Switch with actuating directions 1–4
- ▶ One changeover contact with screw terminal for each actuating direction
- ▶ Bellows



## Technical data

### Approvals



### Electrical connection values

Fuse	T16/F25
Rated insulation voltage $U_i$	250 V
Rated impulse voltage $U_{imp}$	2.5 kV
Utilization category	DC-13 24V 4A AC-15 230V 10A
Switching voltage	min. 24 V
Switching current	(at 24V) min. 50 mA

### Mechanical values and environment

Connection type	Screw terminal
Number of monitoring contacts	4 (4 directions)
Actuating directions	4 (Switch)
Storage temperature	-25 ... 70 °C
Mechanical life	1 x 10 <sup>6</sup>
Mounting cut-out	Ø 42 mm
Switching principle	Changeover contact ZA, IEC 947-5-1 (Snap-action contact element, design ES502V1)
Degree of protection	on the front with bellows IP65
Ambient temperature	-25 ... 65 °C

## Material

Contact Silver alloy  
Switching lever galvanized steel  
Housing thermoplastic/aluminum  
Bellows elastomer, black  
(Low PAH)

## Miscellaneous

Additional feature	Bellows
--------------------	---------