

SN05R12-502LE060-M (Order no. 088757)

Series SN... 12 mm, mechanical

- ▶ Plunger spacing 12 mm
- ▶ Upright housing, small flange
- ▶ Degree of protection IP67 according to IEC 60529
- ▶ LED function display



Switching element


ES 502 E Snap-action switching contact 1 NC + 1 NO

LED function display

Function display is available for the following voltage range

LE060 12 ... 60 V AC/DC

Dimensional drawings



6	84	24
5	72	24
4	60	24
3	48	24
2	36	19
n	l ₃	a

1 Operating point

2 Free position

3 Dog


4 n Number of plungers

5 Operating voltage for indicator LE060 12V-60V (with LED)

6 LED


Connection examples

ES 502 E



Technical data

Approvals



Electrical connection values

Fuse	max. 8 A gG	
Connection cross section	0.34 ... 1.5 mm ²	
Display module	AC/DC 12 ... 60 ... 60 V LED	
Rated insulation voltage U _i	250 V	
Rated impulse voltage U _{imp}	2.5 kV	
Utilization category	AC-12 8 A 250 V AC-15 6 A 230 V DC-13 6 A 24 V	
Switching current	min. at DC 12V min. 10 mA	
thermal rated current I _{th}	8 A	

Mechanical values and environment

Anfahrsgeschwindigkeit	0.01 ... 80 m/min	
Connection type	2 x M20 x 1.5	
Number NC contacts	5	
Number of switching elements	5	
Number of NO contacts	5	
Design	upright	
Actuating element	Slide bearing Roller plunger (Operating point accuracy ± 0.01. The reproducible operating point accuracy	