


STP3D-4141B024SEM4AS1C2340 (Order no. 112007)

Technical data

Approvals



Electrical connection values

ASI operating current	max. 45 mA
AS-Interface auxiliary voltage	20.4 ... 24 ... 26.4 V
Auxiliary current AS-Interface	300 mA
AS-Interface LED	
	green Power
	red Fault
AS-Interface protocol	ASi-3
ASI data out	D0 = control of guard locking, D1 = red LED, D2 = green LED
ASI data in	D0, D1 = door position, D2, D3 = guard locking
AS-Interface slave type	ID-Code: B, EA-Code: 7
ASI voltage	22.5 ... 30 ... 31.6 V
Solenoid duty cycle	100 %

Mechanical values and environment

Anfahrsgeschwindigkeit	max. 20 m/min
Connection type	
	1 x Plug connector M12 (4-pin)
Number of door position positively driven contacts	
	according to AS-i Safety at Work
Number of guard lock monitoring positively driven contacts	
	according to AS-i Safety at Work D2, D3 (1 = locked)
Extraction force	30 N

Actuation frequency	max. 1200 1/h
Actuating force	35 N
Installation orientation	any
Storage temperature	-25 ... 70 °C
Mechanical life	1 x 10 ⁶
Retention force	20 N
Switching principle	Slow-action switching contact
Degree of protection	IP67
Ambient temperature	-20 ... 55 °C
Material	
Contact	Silver alloy, gold flashed
Housing	Reinforced thermoplastic
Locking force F _{max}	2500 N
Locking force F _{Zh}	2000 N
Guard locking principle	Closed-circuit current principle

Characteristic values according to EN ISO 13849-1 and EN IEC 62061

	B10 _D	Mission time
Guard lock monitoring	5x10 ⁶	20 y
Important! Values valid at DC-13 100 mA/24V		

	PL	Maximum SIL	Category	Mission time
Control of guard locking	Depending on external control of guard locking			20 y

Miscellaneous

C number	C2340	With pre-assem. insertion funnel, aligned plug connector
----------	-------	--

In combination with actuator ACTUATOR-S-GT-LN

Horizontal insertion depth	28.5 mm
Vertical insertion depth	28.5 mm