

MGB-H-AA1A6-L-111839 (Order no. 111839)

Handle module MGB-H... with automatically extending lockout mechanism

- ▶ Intelligent bolt tongue
- ▶ Fold-out lockout mechanism
- ▶ Second automatically extending lockout mechanism
- ▶ Door handle
- ▶ Mounting plate



Bolt tongue

The bolt tongue is safely detected by a transponder as soon as it is inserted into the evaluation module.

Lockout mechanism (automatically extending and fold-out)

For cleaning and service on the machine the bolt tongue can be locked with max. 3 padlocks.

The lockout mechanism extends automatically on the actuation of the handle and prevents the operation of the handle in the safe state. In addition, the fold-out lockout mechanism can be used.

Door handle

The MGB has a robust door handle that can be rotated in 90° steps to suit all installations. The actuating direction can be changed very easily for doors hinged on the left or right.

Door knob

As an alternative to the door handle, the handle module can also be equipped with a door knob.

Technical data

Approvals



Mechanical values and environment

Installation orientation	Door hinge DIN left
Storage temperature	-25 ... 70 °C
Degree of protection	IP65
Ambient temperature	-20 ... 55 °C
Material	
	Housing Fiber glass reinforced plastic, nickel-plated die-cast zinc, stainless steel

Miscellaneous

Product version number	V3.0.0
Additional feature	with mounting plate and automatic lockout mechanism