

CKS-A-L1B-SC-158081 (Order no. 158081)

Key adapter CKS

- ▶ Key adapter with integrated CES read head
- ▶ Simple connection via plug connector M8
- ▶ Front cover: black
- ▶ High degree of protection IP67
- ▶ LED indicator



Combination options

Suitable for connection to a CES-AZ-.ES evaluation unit or CES-FD field device **Important:** The key adapter CKS must not be used as a lockout bar in combination with multicode evaluation.

Important: Keys must be ordered separately!

Technical data

Approvals



Workspace

Secured switch-off distance s_{ar}

referred to the end stop for the inserted actuator max. 30 mm
(in conjunction with evaluation unit CES-AZ-xES-xxB)

Secured switching distance s_{a0}

referred to the end stop for the inserted actuator min. 2 mm
(in conjunction with evaluation unit CES-AZ-xES-xxB)

Switching hysteresis

referred to the end stop for the inserted actuator 1 mm
(in conjunction with evaluation unit CES-AZ-xES-xxB)

Operating and display elements

LED display white: valid actuator detected

Electrical connection values

Power supply Via evaluation unit

Mechanical values and environment

Connection type M8 plug connector, 3-pin

Tightening torque

Fixing screws 0.25 ... 0.35 Nm

Installation orientation on the front

Switching frequency see operating instructions for the related evaluation unit

Storage temperature -25 ... 70 °C

Cable length

maximum allowed max. 25 m

Mounting type Mounting using screw clamp elements on rear side

Mounting cut-out 33 x 68 mm

Degree of protection

in mounted condition (only access side) IP65/IP67
(in the installed state)

Ambient temperature -20 ... 70 °C

Material

Housing PA6-GF30

Method of operation inductive