

GLBF03R12-508LE060-M (Order no. 087575)

Technical data

Approvals



Electrical connection values

Fuse	max. 10 A gG	
Connection cross section	0.34 ... 1.5 mm ²	
Display module	AC/DC	12 ... 60 ... 60 V LED
Rated insulation voltage U_i	250 V	
Rated impulse voltage U_{imp}	4 kV	
Utilization category	AC-15	6 A 230 V
	DC-13	6 A 24 V
Switching current		
	min. at DC 24V	min. 10 mA
thermal rated current I_{th}	10 A	

Mechanical values and environment

Anfahrsgeschwindigkeit	0.01 ... 80 m/min	
Connection type	3 x	M25 x 1.5
Number of switching elements	3	
Number of positively driven contacts	3	
Design	horizontal	
Actuating element	Slide bearing	Roller plunger
Actuating force	min. 15 N	
Installation orientation	any	
Storage temperature	-25 ... 80 °C	

Mechanical life	30 x 10 ⁶
Switching principle	Slow-action switching contact
Degree of protection	IP67
Plunger spacing	12 mm
Ambient temperature	-5 ... 80 °C
Material	
	Contact Silver alloy, gold flashed
	Housing Sand-cast aluminum, anodized

Characteristic values according to EN ISO 13849-1 and EN IEC 62061

B _{10D}	20 x 10 ⁶
------------------	----------------------