

## RIEGEL NZ/TZ-ACF (Order no. 083900)

### Bolt for safety switch NZ.VZ and TZ with escape release

- ▶ Bolt with escape release for two safety switches NZ.VZ and TZ with escape release
- ▶ Steel bolt
- ▶ For doors hinged on the right or left
- ▶ Escape release
- ▶ Detent knob in open position
- ▶ Suitable for a door gap of approx. 15 mm



### Scope of delivery

- ▶ Bolt parts
- ▶ Actuator

### To be ordered separately:

- ▶ Safety switch

### Latching in open position

Latching in the open position is intended to prevent persons from trapping themselves in a machine from the inside. The bolt slider is latched in the detent position. Unlock by pulling the detent knob upward.

### Escape release

Bolts with escape release feature an escape lever enabling the bolt to be opened from inside a guard.

### Door types and door hinges

Suitable for hinged or sliding doors Suitable for doors hinged on the left and right With door stop, door cannot be opened inwards.

### Integrated lockout bar

With the aid of the integrated lockout bar, the bolt can be secured in the open position, e.g. using padlocks. It is possible to prevent people from being locked in the danger area unintentionally.



## Technical data

### Mechanical values and environment

Approach direction	A or C
Number of safety switches that can be mounted	2
Escape release	Yes
Storage temperature	-25 ... 70 °C
Material	
Handle	Plastic
Base plate	Galvanized steel
Switch bracket	Steel powder-coated
Guide strips	Plastic

### Miscellaneous

Detent mechanism open position	Bolt detent mechanism
--------------------------------	-----------------------