

**TZ2RE024-C1527 (Order no. 059638)**

## Technical data

### Approvals



### Operating and display elements

LED display

Operating voltage corresponds to the solenoid voltage  
(2 LEDs; green, red)

### Electrical connection values

Fuse	max. 4 A gG (>70 °C =>2 A gG)	
Power consumption	10 W	
Rated insulation voltage $U_i$	250 V	
Rated impulse voltage $U_{imp}$	2.5 kV	
Utilization category		
	AC-15	4 A 230 V (>70 °C =>2 A)
	DC-13	4 A 24 V (>70 °C =>2 A)
Solenoid operating voltage	AC/DC	24 V -15% ... +10%
Solenoid duty cycle	100 %	
Switching voltage		
	min. at 10 mA	12 V
Switching current		
	min. at 24 V	1 mA
thermal rated current $I_{th}$	4 A (>70 °C =>2 A)	

### Mechanical values and environment

Anfahrgeschwindigkeit	max. 20 m/min
-----------------------	---------------

Approach direction

Actuating head left C

Connection type		
	1 x	Cable connection (l = 5,000 mm; positively driven contact for door monitoring contact and positively driven contact for guard lock monitoring in series)
Number of guard lock monitoring NO contacts	1	
Number of door position positively driven contacts	2	
Number of guard lock monitoring positively driven contacts	1	
Extraction force	30 N	
Actuation frequency	max. 1200 1/h	
Actuating force	35 N	
Lid	black	
Installation orientation	any	
Insertion depth	52 mm	
Storage temperature	-25 ... 80 °C	
Mechanical life	1 x 10 <sup>6</sup>	
Retention force	10 N	
Switching principle	Slow-action switching contact	
Degree of protection	IP65	
Ambient temperature	-25 ... 80 °C	
Material		
	Housing	Anodized die-cast alloy
	Contact	Silver alloy, gold flashed
Locking force F <sub>max</sub>	2000 N	
Locking force F <sub>Zh</sub>	1500 N	
Guard locking principle	Open-circuit current principle	

### Characteristic values according to EN ISO 13849-1 and EN IEC 62061

	B10 <sub>D</sub>	Mission time
--	------------------	--------------