

Aluminum Clear/Black Pre-Insulated Power Bars Single-Sided Conductor Entry

Type IPB-S/Type IPBB-S

Manufactured from high strength aluminum alloy

Dual rated for aluminum and copper conductors, 600 Volt, 90°C

Wide conductor range: 750 kcmil - 14 Sol.

- Allows flexibility in the field and reduces number of connectors in inventory

Multiple conductor configurations: 2 through 14 position

- Choose the right connector for the application


Suitable for use in panelboards, cable trays, raceways, ducts and troughs

Pre-filled with oxide inhibitor, prevents oxidation, moisture and contaminants from entering contact area

Supplied with removable access plugs over screw and conductor ports providing protection against contaminants

Pre-insulated at factory with high dielectric strength plastisol

- Black insulation is UV resistant
- Clear insulation allows for visual confirmation that conductor is properly inserted
- Saves time, eliminates taping, reduces overall installation costs
- Abrasion and chemical resistant
- Will not support combustion



SINGLE SIDED ENTRY



CLEAR PART NO.	BLACK PART NO.	NUMBER OF CONDUCTORS	CONDUCTOR RANGE	APPROXIMATE DIMENSIONS (IN.)			
				L	W	H	HEX SIZE
IPB-NA4-2S	IPBB-NA4-2S	2	4 Str. - 14 Sol.	1.39	1.13	1.25	1/8
IPB-NA4-3S	IPBB-NA4-3S	3		1.99	1.13	1.25	
IPB-NA4-4S	IPBB-NA4-4S	4		2.59	1.13	1.25	
IPB-NA4-5S	IPBB-NA4-5S	5		3.19	1.13	1.25	
IPB-NA4-6S	IPBB-NA4-6S	6		3.79	1.13	1.25	
IPB-NA4-8S	IPBB-NA4-8S	8		4.99	1.13	1.25	
IPB-NA4-10S	IPBB-NA4-10S	10		6.19	1.13	1.25	
IPB-NA4-12S	IPBB-NA4-12S	12		7.39	1.13	1.25	
IPB-NA4-14S	IPBB-NA4-14S	14		8.59	1.13	1.25	
IPB-NA2/0-2S	IPBB-NA2/0-2S	2		2/0 Str. - 14 Sol.	1.64	1.32	
IPB-NA2/0-3S	IPBB-NA2/0-3S	3	2.37		1.32	1.38	
IPB-NA2/0-4S	IPBB-NA2/0-4S	4	3.09		1.32	1.38	
IPB-NA2/0-5S	IPBB-NA2/0-5S	5	3.82		1.32	1.38	
IPB-NA2/0-6S	IPBB-NA2/0-6S	6	4.54		1.32	1.38	
IPB-NA2/0-8S	IPBB-NA2/0-8S	8	5.99		1.32	1.38	
IPB-NA2/0-10S	IPBB-NA2/0-10S	10	7.44		1.32	1.38	
IPB-NA2/0-12S	IPBB-NA2/0-12S	12	8.89		1.32	1.38	
IPB-NA2/0-14S	IPBB-NA2/0-14S	14	10.34		1.32	1.38	

