

KCA1E1E1E1E0000DWP189 (Order no. 105798)

Series KC...

- ▶ Tab connector 2.8 x 0.5
- ▶ 4 actuating directions
- ▶ Bellows for panel mounting (W)
- ▶ Bellows for surface mounting (X)



Technical data

Approvals



Electrical connection values

Fuse	T6/F10
Rated insulation voltage U_i	250 V
Rated impulse voltage U_{imp}	2.5 kV
Utilization category	
	DC-13 24V 2A
	AC-15 230V 4A
Switching voltage	min. 10 V
Switching current	
	(at 24V) min. 12 mA

Pushbutton in handle

Utilization category	
	DC-13 24V 0.1A
Switching voltage	min. 10 V
Switching current	
	(at 24V) min. 12 mA

Mechanical values and environment

Connection type	Tab connector 2.8 x 0.5 IEC 760
Number of monitoring contacts	max. 4 4 (4 directions x 1 switching element)
Actuating directions	max. 4 max. 3 positions (0-1-2) possible per type and direction
Storage temperature	-25 ... 70 °C
Mechanical life	1 x 10 ⁶
Mounting cut-out	Ø 52 mm

Switching principle	Changeover contact C, IEC 947-5-1 (Snap-action contact element, design ES556)
---------------------	--

Degree of protection

on the front with bellows IP65
(Version W)

Ambient temperature	-5 ... 65 °C
---------------------	--------------

Material

Bellows elastomer, black
(Low PAH)

Contact Silver alloy

Housing thermoplastic/aluminum

Switching lever galvanized steel

Pushbutton in handle

Mechanical life

(at 0.7A / 250V AC) 0.05 x 10⁶

Switching principle	1 NO contact (4x)
---------------------	-------------------

Miscellaneous

P number	
	P189 (Universal handle with 4 red pushbuttons, cable 5x0.14 mm ² , 500 mm long with plug connector DUBOX socket, 6-pin)

Additional feature

Pushbutton in handle

Bellows W for panel mounting