

WES1234DV (Order no. 018637)

Series WE...

- ▶ Control panel installation at rear or with front plate
- ▶ Switch with actuating directions 1–4
- ▶ One changeover contact with screw terminal for each actuating direction
- ▶ Interlocking in center position
- ▶ Pushbutton in handle



Technical data

Approvals



Electrical connection values

Fuse	T16/F25
Rated insulation voltage U_i	250 V
Rated impulse voltage U_{imp}	2.5 kV
Utilization category	
	DC-13 24V 4A
	AC-15 230V 10A
Switching voltage	min. 24 V
Switching current	
	(at 24V) min. 50 mA

Pushbutton in handle

Utilization category	
	AC-15 230V 2A
	DC-13 24V 1A
Switching voltage	min. 10 V
Switching current	
	(at 24V) min. 12 mA

Mechanical values and environment

Connection type	Screw terminal
Number of monitoring contacts	4 (4 directions)
Actuating directions	4 (Switch)
Storage temperature	-25 ... 70 °C
Mechanical life	1 x 10 ⁶
Mounting cut-out	Ø 42 mm

Switching principle	Changeover contact ZA, IEC 947-5-1 (Snap-action contact element, design ES502V1)
---------------------	---

Degree of protection

on the front without bellows IP54

Ambient temperature	-25 ... 65 °C
---------------------	---------------

Material

Switching lever galvanized steel

Housing thermoplastic/aluminum

Bellows elastomer, black

(Low PAH)

Contact Silver alloy

Pushbutton in handle

Actuating force max. 8 N

Mechanical life

(at 0.7A / 250V AC) 0.05 x 10⁶

Switching principle 1 contact

Miscellaneous

Additional feature	Pushbutton in handle Interlocking
--------------------	--------------------------------------