

## MGB-L1-ARA-AN3A1-M-R-121419 (Order no. 121419)

### Locking module MGB-L1-ARA... (guard locking by spring force) with 2 pushbuttons, key-operated rotary switch, IP54

- ▶ Guard locking with guard lock monitoring
- ▶ Can be connected in series with other AR devices (e.g. CES-AR and CET-AR)
- ▶ Key-operated rotary switch (form L, 90°)
- ▶ 2 pushbuttons (illuminated)
- ▶ With lens set, 6 pcs.
- ▶ With cable entry
- ▶ Unicode
- ▶ Degree of protection IP54



### Guard locking type

MGB- L1... The locking arm is held in the locked position by spring force and is unlocked by solenoid force (closed-circuit current principle, mechanically locked).

### Door hinge

A mechanical door stop is permanently integrated into the evaluation module of the MGB. A marking on the stop makes adjustment easier.

### LED indicator

The LED indicator indicates all important system and status information.

### Monitoring outputs

- OD ON when the door is closed
- OT Bolt tongue inserted into the evaluation module
- OL Guard locking solenoid in locked position
- OI Diagnostics; there is a fault

### Key-operated rotary switch

S1 Key-operated rotary switch with 2 positions (form L, 90°). The key latches in both positions and can be removed in both positions.

### Pushbuttons

- S2 1 NO contact, illuminated
- S3 1 NO contact, illuminated

### Lens set

The color of the pushbuttons can be selected using the color cover set included (5 colors). Item no.: 120344 (see Accessories)