

SPIRALLEITG M STECKVERB 3,9M-106391 (Order no. 106391)

Connecting cable for enabling switch ZSM with plug connector RC17

- ▶ Female plug RC17, 17-pin, and male plug HAN10A, 10-pin
- ▶ Straight plug connector
- ▶ PUR cable
- ▶ Coiled cable
- ▶ Cable length 3.9 m (extended)



Technical data

Electrical connection values

Cable shielding	Yes (Cu thread covering, optical coverage approx. 90%)
specific conductor resistance	max. 145 Ω/km

Mechanical values and environment

Conductor identification	Color code according to DIN 47100
Conductor cross-section	0.14 mm ²
Number of conductors	12
Dynamic bending radius	15 x cable diameter
Static bending radius	10 x cable diameter
Storage temperature	-40 ... 80 °C
Cable type	coiled
Cable diameter	7.5 mm -0,3 ... +0,3 mm
Cable length	3.9 m (extended)
Sheath color	Cable black matte
Drag chain suitability	No
Cable ambient temperature (dynamic)	-10 ... 70 °C
Cable ambient temperature (static)	-40 ... 80 °C

Material

Sheath PUR

Connection 2

Connection type	Plug connector HAN10A
Connection type	Male plug
Plug connector designation	HAN10A (Cable outlet on the bush housing angled)
Number of pins	10
Degree of protection	IP68 (locked)

Connection 1

Connection type	Plug connector RC17
Connection type	Female plug
Plug connector designation	RC17 (Pin 1 to 10 are wired through 1:1)
Number of pins	17
Degree of protection	IP67 (locked)