

RIEGEL CET-A-C/F-C2282 (Order no. 106350)

Bolt for safety switch CET

- ▶ Bolt for switch family CET with escape release
- ▶ Steel bolt
- ▶ Stainless steel guide strip
- ▶ For doors hinged on the left or right
- ▶ With door stop
- ▶ Bolts with escape release
- ▶ Detent knob in open position
- ▶ Suitable for a door gap of approx. 15 mm



Scope of delivery

- ▶ Cover AM-C-124721 for actuator CET

To be ordered separately:

- ▶ Safety switch CET / read head CET.-AX
- ▶ Actuator CET

Latching in open position

Latching in the open position is intended to prevent persons from trapping themselves in a machine from the inside. The bolt slider is latched in the detent position. Unlock by pulling the detent knob upward.

Door types and door hinges

Suitable for hinged or sliding doors Suitable for doors hinged on the left and right With door stop, door cannot be opened inwards.

Integrated lockout bar

With the aid of the integrated lockout bar, the bolt can be secured in the open position, e.g. using padlocks. It is possible to prevent people from being locked in the danger area unintentionally.

Cover

With the cover AM-C-124721, tampering on the CET is effectively prevented. The cover prevents the use of simple tools to manually press up the spring-mounted guard locking pin on the actuator.

Technical data

Mechanical values and environment

Approach direction	A or C
Number of safety switches that can be mounted	1
Escape release	Yes
Storage temperature	-25 ... 70 °C
Material	
Switch bracket	Steel powder-coated
Guide strips	Stainless steel
Base plate	Galvanized steel
Handle	Plastic

Miscellaneous

C number	
C2282	additional mounting holes
Detent mechanism open position	Bolt detent mechanism