

GNBG02R16-502-MC302 (Order no. 086476)

Technical data

Electrical connection values

Fuse	max. 8 A gG	
Connection cross section	0.34 ... 1.5 mm ²	
Rated insulation voltage U _i	250 V	
Rated impulse voltage U _{imp}	2.5 kV	
Utilization category		
	AC-15	6 A 230 V
	DC-13	6 A 24 V
	AC-12	8 A 250 V
Switching current		
	min. at DC 12V	min. 10 mA
thermal rated current I _{th}	8 A	

Mechanical values and environment

Anfahrsgeschwindigkeit	0.01 ... 80 m/min	
Connection type		
	2 x	M20 x 1.5
Number NC contacts	2	
Number of switching elements	2	
Number of NO contacts	2	
Design	upright	
Actuating element		
	Slide bearing	Roller plunger (Operating point accuracy ± 0.01. The reproducible operating point accuracy refers to the axial travel of the plunger after the switching element ES 502 E has been run-in with approx. 2,000 operating cycles.)
Actuating force	min. 20 N	
Installation orientation	any	
Storage temperature	-25 ... 80 °C	
Mechanical life	30 x 10 ⁶	
Contact bounce time	max. 3 ms	

Switching principle	Snap-action switching contact
Schließzeit	max. 4 ms
Degree of protection	IP67
Plunger spacing	16 mm
Ambient temperature	-5 ... 80 °C
Material	
	Housing Sand-cast aluminum, anodized
	Contact Silver alloy, gold flashed

Miscellaneous

C number	
	C302 special casting for Volkswagen AG, safety groove