




C-M12F05-05X034PV20,0-MA-100185 (Order no. 100185)

Connecting cable with straight plug connector M12, 5-pin, 20 m

- ▶ M12 female plug, 5-pin
- ▶ Straight plug connector
- ▶ PVC cable
- ▶ Cable length 20 m
- ▶ With flying lead



Dimensional drawings



1 Female plug M12x1, 5-pin

2 Terminal assignment as seen from the connection side

Technical data

Approvals



Electrical connection values

Rated voltage	DC	60 V
Rated impulse voltage U_{imp}		1.5 kV
Nominal current	at 25 °C	4 A
specific inductance		0.53 mH/km
specific capacitance		100 nF/km
specific conductor resistance		58 Ω /km
Connection 1		
Degree of contamination according to EN 60664-1		3

Mechanical values and environment

Conductor identification	Color code
Conductor cross-section	0.34 mm ²
Number of conductors	5
Dynamic bending radius	15 x cable diameter
Static bending radius	5 x cable diameter
Fire behavior	flame retardant according to UL-Style 2464
Storage temperature	-25 ... 80 °C
Cable type	straight
Cable diameter	approx. 5.9 mm
Cable length	20 m
Sheath color	black
Drag chain suitability	No

Cable ambient temperature (dynamic)	-5 ... 80 °C
Cable ambient temperature (static)	-25 ... 80 °C
UV resistance	moderately UV resistant

Material

Sheath	PVC
Conductor insulation	PVC
Conductor	Cu flexible wire bare

Connection 2

Conductor end	Sheath stripped
Connection type	flying lead

Connection 1

Connection type	Plug connector M12x1
Connection type	Female plug
Tightening torque	0.5 Nm
Insulating material group	I
Cable outlet	straight
Number of pins	5
Degree of protection	IP67 (in the inserted state)
Plug lock	Screw connection
Insertion cycles	100

Material

Plug housing	TPU
Plug lock	CuZn, nickel plated