

Rated voltage	30 V
Nominal current	at 40 °C 4 A
Degree of contamination according to EN 60664-1	3

## Mechanical values and environment

Storage temperature	-30 ... 70 °C
Ambient temperature	-30 ... 55 °C

### Connection 1

Connection type	2x M4 screws
Connection type	Male plug
Number of pins	5
Degree of protection	IP65 (Only in the screwed tight state with the related mating components.)
Insertion cycles	100
Material	
Plug housing	Plastic

### Connection 2

Connection type	Screw terminal
Connection type	Male plug
Type specification	M12 EN 61076-2-101 / A-coded
Number of pins	5
Degree of protection	IP65 (Only in the screwed tight state with the related mating components.)
Insertion cycles	100
Material	
Plug housing	Plastic, die-cast zinc, nickel plated
Plug lock	die-cast zinc, nickel plated



## Connection accessories AC-MC-00-0-B-156718

### Electrical connection values

Degree of contamination according to EN 60664-1	3
---	---

### Mechanical values and environment

Storage temperature	-30 ... 70 °C
---------------------	---------------

Ambient temperature	-30 ... 55 °C
---------------------	---------------

Material	Fiber glass reinforced plastic
----------	--------------------------------

#### Connection 1

Connection type	2x M4 screws
-----------------	--------------

Degree of protection	IP65 (Only in the screwed tight state with the specified base units.)
----------------------	--

### Miscellaneous

Color	black
-------	-------

Additional feature	incl. fixing screws incl. seal
--------------------	-----------------------------------