

G fuse link DIN 41660 quick-response High breaking capacity Rated continuous current 1 A



Model		
product brand name	SETRON	
product designation	G fuse link	
design of the product	quick-response (F)	
type of miniature fuse	ceramic fuse	
General technical data		
size of the fuse link	5 x 20 mm	
melting characteristics	quick acting (F)	
type of voltage of the operating voltage	AC	
operating voltage rated value	250 V	
Main circuit		
operational current rated value	1 A	
Display and operation		
product component visual defect indication	No	
Mechanical Design		
Net Weight	2 g	
Approvals Certificates		
General Product Approval	other	Environment



[Confirmation](#)



[Environmental Con-
firmations](#)

[Environmental Con-
firmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WA1822-7EF16>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8WA1822-7EF16>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA1822-7EF16

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

last modified:

5/26/2025 