



*** spare part *** SIMATIC DP, DP master interface for IM151-7 CPU or IM151-8 PN/DP (ET200S), module with PROFIBUS DP interface (9-pole D-sub socket) as DP master

Interfaces	
PROFIBUS DP	
• Transmission rate, max.	12 Mbit/s; 9,6 / 19,2 / 45,45 / 93,75 / 187,5 / 500 kbit/s; 1,5 / 3 / 6 / 12 Mbit/s
• Cable length, max.	100 m; Shielded
Protocols	
PROFIBUS DP	Yes
Dimensions	
Width	35 mm
Height	119.5 mm
Depth	75 mm
Weights	
Weight, approx.	100 g
Classifications	

	Version	Classification
eClass	14	27-24-26-08
eClass	12	27-24-26-08
eClass	9.1	27-24-26-08
eClass	9	27-24-26-08
eClass	8	27-24-26-08
eClass	7.1	27-24-26-08
eClass	6	27-24-26-08
ETIM	9	EC001604
ETIM	8	EC001604
ETIM	7	EC001604
IDEA	4	3564
UNSPSC	15	32-15-17-05

Approvals / Certificates	
General Product Approval	

[Manufacturer Declaration](#)



[Miscellaneous](#)



EMV	For use in hazardous locations
-----	--------------------------------



RCM



ATEX

[FM](#)



ATEX



UL

[Miscellaneous](#)

For use in hazardous locations

Maritime application



ATEX



IECEX

[CCC-Ex](#)



ABS



BUREAU
VERITAS



DNV

Maritime application



LRS

[NK / Nippon Kaiji Kyokai](#)



PRS



RINA

[CCS \(China Classification Society\)](#)

last modified:

11/5/2024