



Figure similar

Article No. : 6SE6440-2UE33-0EA1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data

Input

Number of phases	3 AC
Line voltage	500 ... 600 V \pm 10 %
Line frequency	47 ... 63 Hz
Rated current (LO)	58.00 A
Rated current (HO)	48.00 A

Output

Number of phases	3 AC
Rated voltage	600 V
Rated power (LO)	37.00 kW / 50.00 hp
Rated power (HO)	30.00 kW / 40.00 hp
Rated current (LO)	52.00 A
Rated current (HO)	41.00 A
Pulse frequency	4,000 Hz
Output frequency for V/f control	0...650 Hz
As a result of legal stipulations, a limit to 550 Hz is in production	

Overload capability

Low Overload (LO)

140 % output current for 3 s, followed by 110 % output current for 57 s followed by 100 % output current for 240 s in a 300 s cycle time

High Overload (HO)

150 % output current for 60 s, followed by 100 % output current for 240 s in a 300 s cycle time

General tech. specifications

Power factor λ	0.95
Efficiency η	0.96

Ambient conditions

Cooling	Fan
---------	-----

Ambient temperature

Operation (LO)	-10...40 °C
Operation (HO)	-10...50 °C
Transport	-40...70 °C
Storage	-40...70 °C



Figure similar

Article No. : 6SE6440-2UE33-0EA1

Mechanical data

Degree of protection	IP20 / UL open type
Frame size	FSE
Net weight	20.00 kg
Width	275.0 mm
Height	650.0 mm
Depth	245.0 mm

Inputs / outputs

Standard digital inputs

Number	6
--------	---

Relay output

Number	3
--------	---

Analog inputs

Number	2
--------	---

Analog outputs

Number	2
--------	---

PTC/ KTY interface

Number	1
--------	---

Connections

Motor end

Conductor cross-section	35.00 mm ²
-------------------------	-----------------------