



Figure similar

**Article No. :** 6SE6440-2UD41-3GA1

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Rated data

#### Input

Number of phases	3 AC
Line voltage	380 ... 480 V $\pm$ 10 %
Line frequency	47 ... 63 Hz
Rated current (LO)	297.00 A
Rated current (HO)	245.00 A

#### Output

Number of phases	3 AC
Rated voltage	480 V
Rated power (LO)	160.00 kW / 250.00 hp
Rated power (HO)	132.00 kW / 200.00 hp
Rated current (LO)	302.00 A
Rated current (HO)	250.00 A
Pulse frequency	4,000 Hz
Output frequency for <i>V/f</i> control	0...267 Hz

#### Overload capability

##### Low Overload (LO)

150 % output current for 1 s, followed by 110 % output current for 59 s followed by 100 % output current for 240 s in a 300 s cycle time

##### High Overload (HO)

136 % output current for 57 s, followed by 100 % output current for 243 s in a 300 s cycle time

### General tech. specifications

Power factor $\lambda$	0.95
Efficiency $\eta$	0.97

### Ambient conditions

Cooling	Fan
---------	-----

#### Ambient temperature

Operation (LO)	0...40 °C
Operation (HO)	0...40 °C
Transport	-40...70 °C
Storage	-40...70 °C



Figure similar

Article No. : 6SE6440-2UD41-3GA1

### Mechanical data

Degree of protection	IP20 / UL open type
Frame size	FSGX
Net weight	174.00 kg
Width	326.0 mm
Height	1,533.0 mm
Depth	545.0 mm

### Inputs / outputs

#### Standard digital inputs

Number	6
--------	---

#### Relay output

Number	3
--------	---

#### Analog inputs

Number	2
--------	---

#### Analog outputs

Number	2
--------	---

#### PTC/ KTY interface

Number	1
--------	---

### Connections

#### Motor end

Conductor cross-section	240.00 mm <sup>2</sup>
-------------------------	------------------------