



*** Spare part *** Electronics module for ET 200S, 8 DI source input 24 V DC, 15 mm width, 1 unit per packing unit

Supply voltage	
Rated value (DC)	24 V; From power module
Reverse polarity protection	Yes
Input current	
from supply voltage L+, max.	Dependent on encoder
Power loss	
Power loss, typ.	1.2 W
Digital inputs	
Number of digital inputs	8
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Input voltage	
• Type of input voltage	DC
• Rated value (DC)	24 V
• for signal "0"	-5 to +30V
• for signal "1"	-15 to -30 V
Input current	
• for signal "1", typ.	6 mA; at 24 V
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	No
— at "0" to "1", min.	2 ms
— at "0" to "1", max.	4.5 ms
— at "1" to "0", min.	2 ms
— at "1" to "0", max.	4.5 ms
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
Interrupts/diagnostics/status information	
Diagnostics function	No
Diagnostics indication LED	
• Group error SF (red)	No
• Status indicator digital input (green)	Yes; per channel
Parameter	
Remark	3 byte
Potential separation	
Potential separation digital inputs	

- between the channels
- between the channels and backplane bus

No
Yes

Isolation

Isolation tested with 500 V DC

Dimensions

Width 15 mm
Height 81 mm
Depth 52 mm

Weights

Weight, approx. 35 g

Classifications

	Version	Classification
eClass	14	27-24-26-04
eClass	12	27-24-26-04
eClass	9.1	27-24-26-04
eClass	9	27-24-26-04
eClass	8	27-24-26-04
eClass	7.1	27-24-26-04
eClass	6	27-24-26-04
ETIM	9	EC001599
ETIM	8	EC001599
ETIM	7	EC001599
IDEA	4	3566
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval



Miscellaneous

Manufacturer Declaration



EMV For use in hazardous locations



FM



For use in hazardous locations Maritime application



Miscellaneous

CCC-Ex



Maritime application



NK / Nippon Kaiji Kyokai



CCS (China Classification Society)

last modified: 5/22/2024