



Rigid Bushings

Insulated - 105°C Thermoplastic Liner - Cast Zinc

Features

- Liner is rated flame retardant to 105°C

Applications


- Indoor or outdoor use
- Use with locknut to terminate Rigid or IMC conduit to an outlet box
- Plastic liner prevents damage to wire insulation

Standard Material

- Zinc
- Plastic insulator

Certifications

- UL File #: E515752



Catalog Number	UPC	Size	Box Qty	Ship Case	Weight (lbs) per 100	Inches	
						A	B
311	11887	1/2"	100	1000	3	1.053	0.394
312	11889	3/4"	50	500	4	1.327	0.394
313	11892	1"	50	500	8	1.584	0.477
314	11893	1-1/4"	25	250	10	1.952	0.503
315	11896	1-1/2"	25	250	11	2.201	0.522
316	11897	2"	10	100	17	2.693	0.564
317	11901	2-1/2"	50	---	40	3.235	0.866
318	11903	3"	25	---	48	3.855	0.866
319	11905	3-1/2"	25	---	56	4.359	0.866
320	11907	4"	10	---	60	5.011	0.866

Nesco Inc.

1039 Cardiff Blvd., Mississauga, ON L5S 1P4

TF: (866) 466-3726 Tel: (905) 793-2218 Fax: (905) 793-2268

www.nescocanada.com

Ref. 1