



EMT Raintight Connectors

Compression Type, Insulated Throat - Steel

Features

- Raintight and concrete tight
- Compression type connectors
- Assembled with a steel locknut & gasket

Applications

- Use to join EMT to box or enclosure in dry or wet locations

Standard Material


- Steel

Standard Finish

- Zinc plated

Certification

- UL File #: E325997



Catalog Number	UPC	Size	Box Qty	Ship Case	Weight (lb) per 100	Inches		
						A	B	C
TRTSCI-05	15574	1/2"	25	250	8	0.689	0.50	1.125
TRTSCI-07	15576	3/4"	25	250	18	0.75	0.50	1.375
TRTSCI-10	15578	1"	20	100	23	0.846	0.562	1.687
TRTSCI-12	15580	1-1/4"	25	---	40	1.687	1.012	2.062
TRTSCI-15	15581	1-1/2"	20	---	54.5	1.717	1.062	2.25
TRTSCI-20	15582	2"	15	---	75	1.875	1.125	2.75
TRTSCI-25	15583	2-1/2"	12	---	119.2	1.968	1.562	3.625
TRTSCI-30	15584	3"	6	---	173	2.689	1.562	4.25
TRTSCI-35	15585	3-1/2"	5	---	238	2.812	1.812	4.687
TRTSCI-40	15586	4"	6	---	264	2.812	1.812	5.187

Nesco Inc.

1039 Cardiff Blvd., Mississauga, ON L5S 1P4
 TF: (866) 466-3726 Tel: (905) 793-2218 Fax: (905) 793-2268
www.nescocanada.com