



BX, Flex Connectors

Straight - Squeeze Type - Zinc Die Cast

Features

- Squeeze type straight
- Available with insulated throat

Applications


- Indoor use only
- In a dry location, use to connect flexible metallic conduit and steel AC cable to a steel outlet box, load center or other metal enclosure
- The 3/8" can also be used with steel and aluminum MC cable
- 3/8" size fits 1/2" knockout

Standard Material

- Zinc die cast

Certifications

- UL File #: E224953



Catalog Number	UPC	Conduit Size	Unit Carton	Ship Case	Weight/ Case	Inches			Screws
						A	B	C: Min-Max	
150Z	16426	3/8" (½" KO)	50	500	35	1.17	1.07	.58-.61	1
151Z	16427	1/2"	50	200	20	1.19	1.45	.74-.95	1
152Z	16428	3/4"	25	100	13	1.43	1.57	.88-1.11	1
153Z	16429	1"	10	100	20	1.70	1.67	1.14-1.38	1
154Z	16430	1-1/4"	10	100	29	1.96	1.81	1.42-1.65	1
155Z	16431	1-1/2"	5	50	20	2.30	2.37	1.68-1.94	1
156Z	16432	2"	10	---	---	2.83	2.5	2.08-2.56	1
157Z	16433	2-1/2"	5	---	---	3.46	2.91	2.85-3.25	2
158Z	16434	3"	5	---	---	4.01	3.03	3.33-3.63	2
159Z	16435	3-1/2"	5	---	---	4.57	3.8	3.75-4.10	2
160Z	16436	4"	5	---	---	5.11	4.27	4.18-4.58	2

Nesco Inc.

1039 Cardiff Blvd., Mississauga, ON L5S 1P4

TF: (866) 466-3726 Tel: (905) 793-2218 Fax: (905) 793-2268

www.nescocanada.com