Plugs

Fed. Spec.

Poles/Wires	Rating		15A	20A	30A
2P/3W	125V		HBL4720CST	HBL2311ST*	HBL2611ST*
	250V		HBL4570CST	HBL2321ST*	HBL2621ST*
	277V		HBL4770CST	HBL2331ST	—
	480V		—	HBL2341ST	—
3P/4W	125/250V		—	HBL2411ST*	HBL2711ST*
	3Ø 250V		—	HBL2421ST	HBL2721ST
	3Ø 480V		—	HBL2431ST	HBL2731ST
4P/5W	250V/600V		—	HBL3521CST	—
	3ØY 120/208V		—	HBL2511ST*	HBL2811ST*
	3ØY 277/480V		—	HBL2521ST	HBL2821ST

*Note: *Available in all black - example: HBL2311STBK.*

Connectors

Fed. Spec.

Poles/Wires	Rating		15A	20A	30A
2P/3W	125V		HBL4729CST	HBL2313ST*	HBL2613ST*
	250V		HBL4579CST	HBL2323ST*	HBL2623ST*
	277V		HBL4779CST	HBL2333ST*	—
	480V		—	HBL2343ST	—
3P/4W	125/250V		—	HBL2413ST*	HBL2713ST*
	3Ø 250V		—	HBL2423ST	HBL2723ST
	3Ø 480V		—	HBL2433ST	HBL2733ST
4P/5W	250V/600V		—	HBL3523CST	—
	3ØY 120/208V		—	HBL2513ST*	HBL2813ST*
	3ØY 277/480V		—	HBL2523ST	HBL2823ST

*Note: *Available in all black - example: HBL2313STBK.*

Weatherproof Boots for Insulgrip® Twist-Lock EdgeConnect Devices

IP55 SUITABILITY

Description			Black	Yellow
Weatherproof, Seal-Tite® triple seal elastomer boots.	For 15A devices.	For plugs used in a cord set and connector bodies used with a flanged inlet.	HBL6023ST	HBL60CM23ST
		For connector bodies when used in cord sets	HBL6024ST	HBL60CM24ST
	For 3 wire devices.	For plugs used in a cord set and connector bodies used with a flanged inlet.	HBL6031ST	HBL6035ST
		For connector bodies when used in cord sets.	HBL60CM31ST	HBL60CM35ST
	For 4 & 5 wire devices.	For plugs used in a cord set and connector bodies used with a flanged inlet.	HBL6032ST	HBL6036ST
		For connector bodies when used in cord sets.	HBL60CM32ST	HBL60CM36ST

Dimensions in Inches (mm)