# GUAC2-W



SmartlockPro® GFCI / 24W USB Outlet , Type A / C Charging Ports, 20A Self-Grounding Receptacle - White

20 Amp, 125 Volt Self-Test SmartlockPro® Tamper Resistant GFCI Outlet, 24W (4.8 Amp) USB Charger with Dual 12W Type A / 12W Type C Ports, Back and Side Wire NEMA Self-Grounding 5-20R Receptacle, White with Indicator Light

- SAFE – Delivers continuous NEC® required GFCI protection that automatically self-tests to ensure it can respond to a ground fault with status indicator light for intuitive feedback
- FAST CHARGING - Smart chip technology provides over 2X the charging power of other GFCI USB outlets for a faster charge
- CONVENIENT – No more searching for charging adapters! Charge electronics while leaving the outlets free for additional power needs, requires extra deep wall box
- ENHANCED SAFETY – Overcurrent protection helps protect electronic devices from over charging / heating, and tamper-resistant shutters prevent unwanted objects from being inserted into the outlets
- SMARTLOCKPRO – Patented Lockout Action prevents reset if GFCI is damaged and cannot respond to a ground fault

**Color :** White

**UPC Code :** 78477996119

**Country Of Origin :** Mexico - Pending

**NEMA :** 5-20R

**Available Colors :**

Black

Light Almond

## Technical Information

Electrical Specifications

**Amperage :** 20 A

**Dielectric Voltage :** 1250 VAC

**Grounding :** Self-Grounding

**Horsepower Rating :** 1 hp

**Pole(s) :** 2

**Power Supply Input and Frequency :** 125V, 60Hz

**Temperature Rise :** Max 30°C

**Trip Level :** Class A

**Voltage :** 125 VAC

**Wire(s) :** 5

Environmental Specifications

**Flammability Rating :** UL94, 5VA

**Operating Temperature :** Maximum Continuous 40°C, Minimum -10°C (w/o impact)

Material Specifications

**Body Material :** Thermoplastic

**Face Material :** Thermoplastic

**Line Contacts :** Brass

**Mounting Strap :** Galvanized Steel

**TR Shutter :** Thermoplastic

Mechanical Specifications

**Product ID :** Ratings are marked on device

**Screw Terminal Torque :** No Terminal Screws

**Termination :** Leaded

**Wire Accomodation :** Leaded

Product Features

**Brand :** SmartlockPro

**Color :** White

**Feature(s) :** Indicator Light, Self-Test, Tamper Resistant

**Grade :** Residential /Commercial Specification Grade

**NEMA Configuration :** 5-20R

**Type :** GFCI 24W Type A / C USB Receptacle Outlet

**USB Power Delivery :** No

Standards and Certifications

**Applicable Standards & Certifications :** ANSI C-73, CSA C22.2 No. 42, CSA C22.2 No. 144, FCC Part 15 Class B, Fed Spec WC-596, cCSAus Listed, NOM, UL 1310, UL 498

**NEMA :** WD-1 and WD-6

Warranty

**Warranty :** 1-Year Limited

## Features and Benefits

- Provides continuous ground fault protection – detects and trips on actual ground fault even when self-test is being conducted
- On initial power up, tests the GFCI within 3 seconds
- Auto-monitoring exceeds the UL requirement
- Auto adapts and shifts to more frequent testing if potential problem is detected
- Status Indicator Light provides simple, intuitive feedback on power and protection status as well as indication of line/load reversal
- Patented Lockout Action prevents reset if GFCI is damaged and cannot respond to a ground fault
- Smart chip technology recognizes and optimizes the charging requirements of individual devices including Apple, Samsung, Nexus, Pixel and more
- One Type A Port and one Type-C Port with combined total of 5.1A of charging power
- Tamper-Resistant improves child safety – built-in shutter prevents access by most non-rated/foreign objects
- USB Ports tested to withstand over 10,000 insertions
- Charges most Type A and Type-C USB powered devices
- Type-C Port permits the cables to be inserted easily in either direction
- Charging time may be affected by the charge cord used. Leviton recommends using the cord provided with the device
- Compatible with USB 3.1, 3.0, 2.0, 1.1 devices
- No data transfer capability
- Compatible with Decora® wallplates and Decora Plus™ screwless wallplates. Wallplate sold separately

## Patents*

CA2621644
MX308495
US10483066
US9276393
US9368982
US11831139
US9053886
US11349293
MX338817
US8587914

| | |
|---|---|
| US9496726 | US8242362 |
| US7355117 | MX302458 |
| US8599522 | CA2624409 |
| MX344697 | CA2730014 |
| US7820909 | US11456138 |
| US7697252 | CA2857863 |
| CA2677283 | US7868719 |

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

## SPECIFICATION SUBMITTAL

| | |
|---|---|
| JOB NAME: | CATALOG NUMBERS: |
| JOB NUMBER: | |

**Leviton Manufacturing Co., Inc**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 · FAX: +1-800-824-3005 ·

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52) 5386- 1797 ·

**Visit our Website at: www.leviton.com**

© 2026 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to: www.leviton.com/company/about-leviton/locations

**© 2026 Leviton Manufacturing Co., Inc.**