SIEMENS

Data sheet 6GT2891-0PH50

product type designation	**Adaptor cable for power supply, M12-8 / M12-4**
product description	Highly flexible cable (6-wire)
	SIMATIC RF600 connecting cable for 24 V connection of the readers RF610XR, RF650R, RF68XR to the power supply units of type 6GT2898-0AA and 6GT2898-0AC, PUR, length 5 m.



product brand name	SIMATIC RF
Technical Product Detail Page	https://i.siemens.com/1P6GT2891-0PH50
suitability for use	Plug-in cable for connecting a 24 V power supply to a reader RF61XR, RF650R, RF68XR, MV440
cable designation	L-YC11Y 6x1x0.25 6x24AWG CM
wire length	5 m
electrical data	
number of electrical connections	2
loop resistance per length / maximum	160 mΩ/m
insulation resistance coefficient	20 GΩ·m
operating voltage / maximum	300 V
mechanical data	
design of the shield	Braided shield made of tin-plated copper wires
number of electrical cores	6
type of electrical connection	M12 (male, 4-pin, straight) / M12 (female, 8-pin, straight)
outer diameter	
● of cable sheath	5.4 mm
symmetrical tolerance of the outer diameter / of cable sheath	0.2 mm
design of stranding element	Six
conductor class	5
material	
● of the conductor	CU, blank
● of the wire insulation	PVC
● of cable sheath	PUR
marking / of cores	Color
color	
● of the insulation of data wires	DIN 47100
● of cable sheath	Black
bending radius	
● with single bend / minimum permissible	21.6 mm
● with multiple bends / minimum permissible	43 mm
● with continuous bending	75 mm
number of bending cycles	3000000
tensile load / maximum	200 N
weight per length	45 kg/km
ambient conditions	
ambient temperature	

Subject to change without notice
© Copyright Siemens

● during operation	-30 ... +80 °C
● during storage	-30 ... +80 °C
● during transport	-30 ... +80 °C
● during installation	-30 ... +80 °C
fire behavior	Flame-resistant according to IEC 60332-1-4
chemical resistance	
● to mineral oil	resistant
● to grease	resistant
radiological resistance / to UV radiation	resistant
product features, product functions, product components / general	
product feature	
● halogen-free	No
● silicon-free	Yes
standards, specifications, approvals	
UL/ETL listing / 300 V Rating	Yes; CM
further information / internet links	
internet link	
● to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358
● to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
● to website: Industrial communication	https://www.siemens.com/simatic-net
● to web page: identification and localization systems	https://www.siemens.com/ident
● to web page: SiePortal	https://sieportal.siemens.com/
● to website: Image database	https://www.automation.siemens.com/bilddb
● to website: CAx-Download-Manager	https://www.siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

Approvals / Certificates

General Product Approval					EMV
CE EG-Konf.	UKCA	EAC	China RoHS	Manufacturer Declaration	KC

last modified: 3/10/2026

Subject to change without notice
© Copyright Siemens