SIEMENS

Data sheet 3TX7402-3H

Surge suppressor Varistor with cable spacer 48-127 V AC / 70-150 V DC for mounting to coil terminal for contactors size S0-S2

product category	Surge suppressor
product designation	Varistor
product type designation	3TX7
suitability for use	for 3TH4
General technical data	
certificate of suitability	CE / UL / CSA
Substance Prohibitance (day/month/year)	03/01/2017
Net Weight	0.015 kg
type of voltage of the control supply voltage	AC/DC
control supply voltage at AC	
● at 50 Hz rated value	48 ... 127 V
● at 60 Hz rated value	48 ... 127 V
control supply voltage frequency	
● **1 rated value**	50 Hz
● **2 rated value**	60 Hz
control supply voltage at DC rated value	70 ... 150 V
design of the surge suppressor	Varistor
Ambient conditions	
ambient temperature	
● during operation	-25 ... +55 °C
● during storage	-40 ... +80 °C

Approvals Certificates

Environment	General Product Approval	other
Environmental Confirmations	cULus, EAC, CE EG-Konf., UKCA	Confirmation

other

产品合格 QC PASS

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875

Subject to change without notice
© Copyright Siemens

Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TX7402-3H
Cax online generator
https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX7402-3H
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3TX7402-3H
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX7402-3H&lang=en

---

last modified: 4/2/2025

Subject to change without notice
© Copyright Siemens