SIEMENS

Data sheet 6ES7361-3CA01-0AA0



Figure similar

spare part SIMATIC S7-300, connection IM 361 in expansion rack for connection to central rack (IM360), supply voltage 24 V DC, with C-bus

Supply voltage	
Rated value (DC)	
● 24 V DC	Yes
Input current	
from supply voltage L+, max.	500 mA
Power loss	
Power loss, typ.	5 W
Hardware configuration	
Number of interfaces per CPU, max.	3
Dimensions	
Width	80 mm
Height	125 mm
Depth	120 mm
Weights	
Weight, approx.	505 g
Classifications	

	Version	Classification
eClass	16	27-24-22-08
eClass	14	27-24-22-08
eClass	12	27-24-22-08
eClass	9.1	27-24-22-08
eClass	9	27-24-22-08
eClass	8	27-24-22-08
eClass	7.1	27-24-22-08
eClass	6	27-24-22-08
ETIM	10	EC001423
ETIM	9	EC001423
ETIM	8	EC001423
ETIM	7	EC001423
IDEA	4	3564
UNSPSC	15	32-15-17-05

Approvals / Certificates	
General Product Approval	

Subject to change without notice
© Copyright Siemens

CE EG-Konf.	UKCA	Manufacturer Declaration	UL	RCM	EAC

General Product Approval	EMV	For use in hazardous locations		
Manufacturer Declaration	RCM	ATEX	FM	UL	IECEx

For use in hazardous locations			Maritime application		
ATEX	Miscellaneous	CCC-Ex	ABS	BUREAU VERITAS	DNV

Maritime application				
LRS	NK / Nippon Kaiji Kyokai	PRS	RINA	CCS (China Classification Society)

last modified: 4/7/2025

Subject to change without notice
© Copyright Siemens