

Siemens  
EcoTech



SIRIUS soft starter S0 38 A, 18.5 kW/400 V, 40 °C 200-480 V AC, 110-230 V  
AC/DC Screw terminals

### General technical data

|                                                                                            |                          |
|--------------------------------------------------------------------------------------------|--------------------------|
| product brand name                                                                         | SIRIUS                   |
| product designation                                                                        | Soft starter             |
| product feature                                                                            |                          |
| • integrated bypass contact system                                                         | Yes                      |
| • thyristors                                                                               | Yes                      |
| product function                                                                           |                          |
| • intrinsic device protection                                                              | No                       |
| • motor overload protection                                                                | No                       |
| • evaluation of thermistor motor protection                                                | No                       |
| • external reset                                                                           | No                       |
| • adjustable current limitation                                                            | No                       |
| • inside-delta circuit                                                                     | No                       |
| product component motor brake output                                                       | No                       |
| insulation voltage rated value                                                             | 600 V                    |
| degree of pollution                                                                        | 3, acc. to IEC 60947-4-2 |
| blocking voltage of the thyristor maximum                                                  | 1 600 V                  |
| reference code according to EN 61346-2                                                     | Q                        |
| reference code according to DIN 40719 extended according to IEC 204-2 according to IEC 750 | G                        |

### Power Electronics

|                                                                                                                |               |
|----------------------------------------------------------------------------------------------------------------|---------------|
| operational current                                                                                            |               |
| • at 40 °C rated value                                                                                         | 38 A          |
| • at 50 °C rated value                                                                                         | 34 A          |
| • at 60 °C rated value                                                                                         | 31 A          |
| yielded mechanical performance for 3-phase motors                                                              |               |
| • at 230 V                                                                                                     |               |
| — at standard circuit at 40 °C rated value                                                                     | 11 kW         |
| • at 400 V                                                                                                     |               |
| — at standard circuit at 40 °C rated value                                                                     | 18.5 kW       |
| yielded mechanical performance [hp] for 3-phase AC motor at 200/208 V at standard circuit at 50 °C rated value | 10 hp         |
| operating frequency rated value                                                                                | 50 ... 60 Hz  |
| relative negative tolerance of the operating frequency                                                         | -10 %         |
| relative positive tolerance of the operating frequency                                                         | 10 %          |
| operating voltage at standard circuit rated value                                                              | 200 ... 480 V |
| relative negative tolerance of the operating voltage at                                                        | -15 %         |

|                                                                                                                       |                                                                                                                        |
|-----------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| <b>standard circuit</b>                                                                                               |                                                                                                                        |
| <b>relative positive tolerance of the operating voltage at standard circuit</b>                                       | 10 %                                                                                                                   |
| <b>minimum load [%]</b>                                                                                               | 10 %                                                                                                                   |
| <b>continuous operating current [% of I<sub>e</sub>] at 40 °C</b>                                                     | 115 %                                                                                                                  |
| <b>power loss [W] at operational current at 40 °C during operation typical</b>                                        | 19 W                                                                                                                   |
| <b>Control circuit/ Control</b>                                                                                       |                                                                                                                        |
| <b>type of voltage of the control supply voltage</b>                                                                  | AC/DC                                                                                                                  |
| <b>control supply voltage frequency 1 rated value</b>                                                                 | 50 Hz                                                                                                                  |
| <b>control supply voltage frequency 2 rated value</b>                                                                 | 60 Hz                                                                                                                  |
| <b>relative negative tolerance of the control supply voltage frequency</b>                                            | -10 %                                                                                                                  |
| <b>relative positive tolerance of the control supply voltage frequency</b>                                            | 10 %                                                                                                                   |
| <b>control supply voltage 1 at AC at 50 Hz</b>                                                                        | 110 ... 230 V                                                                                                          |
| <b>control supply voltage 1 at AC at 60 Hz</b>                                                                        | 110 ... 230 V                                                                                                          |
| <b>relative negative tolerance of the control supply voltage at AC at 50 Hz</b>                                       | -15 %                                                                                                                  |
| <b>relative positive tolerance of the control supply voltage at AC at 50 Hz</b>                                       | 10 %                                                                                                                   |
| <b>relative negative tolerance of the control supply voltage at AC at 60 Hz</b>                                       | -15 %                                                                                                                  |
| <b>relative positive tolerance of the control supply voltage at AC at 60 Hz</b>                                       | 10 %                                                                                                                   |
| <b>control supply voltage 1 at DC</b>                                                                                 | 110 ... 230 V                                                                                                          |
| <b>relative negative tolerance of the control supply voltage at DC</b>                                                | -15 %                                                                                                                  |
| <b>relative positive tolerance of the control supply voltage at DC</b>                                                | 10 %                                                                                                                   |
| <b>display version for fault signal</b>                                                                               | red                                                                                                                    |
| <b>Mechanical data</b>                                                                                                |                                                                                                                        |
| <b>size of engine control device</b>                                                                                  | S0                                                                                                                     |
| <b>width</b>                                                                                                          | 45 mm                                                                                                                  |
| <b>height</b>                                                                                                         | 125 mm                                                                                                                 |
| <b>depth</b>                                                                                                          | 150 mm                                                                                                                 |
| <b>fastening method</b>                                                                                               | screw and snap-on mounting                                                                                             |
| <b>mounting position</b>                                                                                              | With vertical mounting surface +/-10° rotatable, with vertical mounting surface +/- 10° tiltable to the front and back |
| <b>required spacing with side-by-side mounting</b>                                                                    |                                                                                                                        |
| • upwards                                                                                                             | 60 mm                                                                                                                  |
| • at the side                                                                                                         | 15 mm                                                                                                                  |
| • downwards                                                                                                           | 40 mm                                                                                                                  |
| <b>wire length maximum</b>                                                                                            | 300 m                                                                                                                  |
| <b>number of poles for main current circuit</b>                                                                       | 3                                                                                                                      |
| <b>Connections/ Terminals</b>                                                                                         |                                                                                                                        |
| <b>type of electrical connection</b>                                                                                  |                                                                                                                        |
| • for main current circuit                                                                                            | screw-type terminals                                                                                                   |
| • for auxiliary and control circuit                                                                                   | screw-type terminals                                                                                                   |
| <b>number of NC contacts for auxiliary contacts</b>                                                                   | 0                                                                                                                      |
| <b>number of NO contacts for auxiliary contacts</b>                                                                   | 1                                                                                                                      |
| <b>number of CO contacts for auxiliary contacts</b>                                                                   | 0                                                                                                                      |
| <b>type of connectable conductor cross-sections for main contacts for box terminal using the front clamping point</b> |                                                                                                                        |
| • solid                                                                                                               | 2x (1 ... 2.5 mm²), 2x (2.5 ... 6 mm²)                                                                                 |
| • finely stranded with core end processing                                                                            | 2x (1 ... 2.5 mm²), 2x (2.5 ... 6 mm²)                                                                                 |
| <b>type of connectable conductor cross-sections for AWG cables for main contacts for box terminal</b>                 |                                                                                                                        |
| • using the front clamping point                                                                                      | 1x 8, 2x (16 ... 10)                                                                                                   |
| <b>type of connectable conductor cross-sections for auxiliary contacts</b>                                            |                                                                                                                        |
| • solid                                                                                                               | 2x (0.5 ... 2.5 mm²)                                                                                                   |
| • finely stranded with core end processing                                                                            | 2x (0.5 ... 1.5 mm²)                                                                                                   |

|                                                                                                                     |                |
|---------------------------------------------------------------------------------------------------------------------|----------------|
| <b>type of connectable conductor cross-sections for AWG cables</b>                                                  |                |
| <ul style="list-style-type: none"> <li>• for auxiliary contacts</li> </ul>                                          | 2x (20 ... 14) |
| <ul style="list-style-type: none"> <li>• for auxiliary contacts finely stranded with core end processing</li> </ul> | 2x (20 ... 16) |

### Ambient conditions

|                                                                |                                                                                                               |
|----------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|
| <b>installation altitude at height above sea level</b>         | 5 000 m                                                                                                       |
| <b>environmental category</b>                                  |                                                                                                               |
| • during transport according to IEC 60721                      | 2K2, 2C1, 2S1, 2M2 (max. fall height 0.3 m)                                                                   |
| • during storage according to IEC 60721                        | 1K6 (only occasional condensation), 1C2 (no salt mist), 1S2 (sand must not get inside the devices), 1M4       |
| • during operation according to IEC 60721                      | 3K6 (no formation of ice, no condensation), 3C3 (no salt mist), 3S2 (sand must not get into the devices), 3M6 |
| <b>ambient temperature</b>                                     |                                                                                                               |
| • during operation                                             | -25 ... +60 °C                                                                                                |
| • during storage                                               | -40 ... +80 °C                                                                                                |
| <b>derating temperature</b>                                    | 40 °C                                                                                                         |
| <b>protection class IP on the front according to IEC 60529</b> | IP20                                                                                                          |
| <b>touch protection on the front according to IEC 60529</b>    | finger-safe, for vertical contact from the front                                                              |

### UL/CSA ratings

|                                                                                                                                                                                                                                                                                                                                                                           |                           |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|
| <p><b>yielded mechanical performance [hp] for 3-phase AC motor</b></p> <ul style="list-style-type: none"> <li>• <b>at 220/230 V</b> <ul style="list-style-type: none"> <li>— at standard circuit at 50 °C rated value</li> </ul> </li> <li>• <b>at 460/480 V</b> <ul style="list-style-type: none"> <li>— at standard circuit at 50 °C rated value</li> </ul> </li> </ul> | <p>10 hp</p> <p>25 hp</p> |
| <b>contact rating of auxiliary contacts according to UL</b>                                                                                                                                                                                                                                                                                                               | B300 / R300               |

## Approvals Certificates

| Environmental Product Declaration                          |          |
|------------------------------------------------------------|----------|
| • global warming potential [CO2 eq] / during manufacturing | 11 kg    |
| • global warming potential [CO2 eq] / during sales         | 0.151 kg |
| • global warming potential [CO2 eq] / during operation     | 128 kg   |
| • global warming potential [CO2 eq] / after end of life    | -2.27 kg |
| • global warming potential [CO2 eq] / total                | 137 kg   |

## Environment

## General Product Approval

### Environmental Con- firmations



**Siemens  
EcoTech**



EAD

|                                                                                                 |                                                                                     |                                                                                     |                                                                                            |
|-------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|
| General Product Approval                                                                        | EMV                                                                                 | Test Certificates                                                                   | other                                                                                      |
| <br>EG-Konf. |  |  | <br>RCM |
|                                                                                                 |                                                                                     | <a href="#">Type Test Certificates/Test Report</a>                                  | <a href="#">Confirmation</a>                                                               |

## other

## Miscellaneous



### Further information

### Simulation Tool for Soft Starters (STS)

<https://support.industry.siemens.com/cs/ww/en/view/101494917>

### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

**Information for data generation and storage**

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW3028-1BB14>

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW3028-1BB14>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW3028-1BB14>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RW3028-1BB14&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW3028-1BB14&lang=en)



