



busbar system, accessory busbar center-to-center spacing 60 mm N/PE busbar support for busbars 12x 5 (10)-30x 5 -10 and 6x 6 mm, free-standing installation or mounting on 8US1923-2AA01

Model	
product brand name	SETRON
product designation	Busbar support
design of the product	N/PE
operating voltage at AC rated value	690 V
suitability for use	Flat bars
type of connectable conductor cross-sections for copper conductor stranded	12 mm x 5 mm - 30 mm x 10 mm

Mechanical Design	
busbar center-to-center spacing	60 mm
Net Weight	52 g

Approvals Certificates	
Environment	General Product Approval

[Environmental Confirmations](#)

[Environmental Confirmations](#)



[Confirmation](#)

General Product Approval	Test Certificates	other			
		Miscellaneous	Miscellaneous	Confirmation	

Further information
Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,...) https://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8US1923-1AA01
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/8US1923-1AA01
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8US1923-1AA01
CAX-Online-Generator https://www.siemens.com/cax
Tender specifications https://www.siemens.com/specifications

Kennlinien

<https://curves.simaris.siemens.com/curves/8US1923-1AA01>

last modified:

6/1/2026 

