



circuit breaker VL150X UL, type CG (cat no. NCX3B030) non-interchangeable frame, with circuit breaker approval acc. to UL 489 standard breaking capacity 3-pole, NEMA rating 35kA/480V (molded case circuit breaker) Electronic Trip Unit TM, LI function TA=40°C In=<30A rated current II=300A short-circuit protection IR=30A Electronic Trip Unit for line protection without connection accessories without auxiliary release without auxiliary/alarm switch, spare part product only for replacement purposes

Weight	2 kg
Net Weight	2 kg

Approvals / Certificates

Environment	General Product Approval
-------------	--------------------------

[Environmental Con-
firmations](#)

[Environmental Con-
firmations](#)



[Confirmation](#)



Test Certificates	other
-------------------	-------

[Special Test Certific-
ate](#)



[Confirmation](#)

[Miscellaneous](#)

Further information

Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
Information for data generation and storage
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
Information- and Downloadcenter (catalogues, leaflets,...)
<https://www.siemens.com/energy-automation>
Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL1103-1KM30-0AA0>
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3VL1103-1KM30-0AA0>
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL1103-1KM30-0AA0
CAx-Online-Generator
<https://www.siemens.com/cax>
Kennlinien
<https://curves.simaris.siemens.com/curves/3VL1103-1KM30-0AA0>



last modified: 11/24/2025

