
Type 12 Mild Steel Pushbutton Enclosures *1437 Series*

Extra Deep





Application

- Designed to accept standard heavy duty oil tight pushbuttons, switches and pilot lights.
- Provides protection from dirt, dust, oil and water.

Standards

- UL 508A Type 12 and 13
- CSA Enclosure 12 and 13
- **Complies with**
  - NEMA Type 12 and 13
  - IEC 60529, IP54
- Appropriate components are required to maintain these standards.

Construction

- Formed from 16 gauge steel.
- Smooth continuously welded seams.
- Welded brackets provide for enclosure mounting.
- Captive cover screws fasten into threaded, sealed wells.
- Larger enclosures provide internally hinged removable covers, designed to hold the cover open during wiring (see drawings).
- Oil resistant gasket and adhesive.
- A bonding stud is provided on the door and a grounding stud is provided on the enclosure.

Finish

- Cover and enclosure are phosphatized and finished in ANSI 61 gray powder coating.

Accessories

- Hole Plugs
- General Accessories

New and improved PDF part drawing files with more detail now available.
Click part number in table below to access PDF, DXF, and STEP files.

30.5mm PB Part No.	22.5mm PB Part No.	No. of Holes	Enclosure H	W	D
1437A[1]	1437MA[1]	1	4.00	4.00	4.75
1437B	1437MB	2	6.00	4.00	4.75
1437C	1437MC	3	8.00	4.00	4.75
1437D	1437MD	4	10.00	4.00	4.75

30.5mm PB Part No.	22.5mm PB Part No.	No. of Holes	Enclosure H	W	D
1437F	**1437MF**	4	7.25	6.25	4.75
1437H	**1437MH**	6	9.50	6.25	4.75
1437K	**1437MK**	9	9.50	8.50	4.75
1437O	**1437MO**	12	11.75	8.50	4.75
1437S	**1437MS**	16	11.75	10.75	4.75
1437V	**1437MV**	20	14.00	10.75	4.75
1437X	**1437MX**	25	14.00	13.00	4.75

[1] Not hinged

Tags: **pushbutton**, **deep**, **Type 12**, **button**, **dial**, **switch**, **pilot light**, **heavy duty**

Data subject to change without notice.

© 2026. Hammond Manufacturing Ltd. All rights reserved.