ESL01-1LW



Decora Lever Edge Rocker Slide Dimmer Switch

Replacing a light switch with a Decora Lever Edge Rocker Slide dimmer switch is now faster and easier. The dimmer offers superior dimming performance with LED bulbs, and a faster, easier installation using Lever Edge terminals. The ESL01 dimmer is rated for 120V 60Hz 150W LED, CFL, and Incandescent lighting. It can be used in single pole or 3-way installations. The dimmer works with existing wiring, no neutral wire required for installation and is ideal for newer and older homes. The dimmer includes a setup button to easily adjust settings such as dimming range, fade on, startup configuration; use with Decora Midway or standard wallplates (sold separately – White).

- PERFORMANCE YOU CAN TRUST - Affordable control engineered to match the performance of high-end dimmers.
- LED ADVANCED - Superior dimming of LED bulbs and fixtures ensures flicker-free lighting
- CUSTOMIZABLE - Setup button to optionally adjust dimmer settings and fine-tunes performance, including minimum dim, maximum bright, fade on, and startup configuration
- INSTALLATION IS A BREEZE - Install with confidence with simple-to-understand color-coded levers and an audible “click” confirming a secure connection, allowing you to wire up to 3.5X faster than traditional devices. A neutral wire is not required for installation.
- PEACE OF MIND KNOWING THAT CONNECTIONS ARE SAFE AND RELIABLE - The push-in Lever Edge terminals securely hold the wires in place
- 3-WAY CONTROL - Convenient control of the same lights from two separate locations; use the dimmer in one location and a 3-way switch (sold separately) in the second location

Color : White

UPC Code : 078477021989

Country Of Origin : China

Technical Information

Product Features

Color : White

Device Type : Dimmer

Grade : Residential

Brand : Decora Slide

Action : Rocker Switch for ON /OFF, slide bar for lighting level control

Available Colors : Ivry-I Wht-W Gry-G Blk-E Brwn-B Light Almond-T, R-Red

Light : Locator light that can be turned off

Preset : Set the Slide bar to maintain the desired lighting level

Electrical Specifications

Load Rating : 150W LED, 150W CFL, 150W Incandescent

Load Type : Dimmable LED, Dimmable CFL, Incandescent

Voltage : 120VAC

Frequency : 60 Hz

Grounding : Self-Grounding

Style Name : Decora Slide

Switch Type : Single-Pole & 3-Way

Wallplate : Order Separately

Type : Rocker Slide Dimmer Switch

Mechanical Specifications

Actuator Material : Thermoplastic

Body Material : Thermoplastic

Strap Material : Plastic

Protection : Radio/TV Filter

Material Specifications

Terminal Accom. : Side Lever Wire #14-#12 AWG; Stranded and Solid copper wire only

Terminal ID : Color Coded Lever Terminals, including Ground

Termination : Color-Coded Levers

Standards and Certifications

Standards and Certifications : cULus, FCC/IC, Title 24, IECC, SSL7A

Warranty

Warranty : 1-Year Limited

Features and Benefits

Dimmer Features

- Integrated slider to brighten and dim lights
- No neutral wire required for installation
- Separate On/Off Decora switch to set and keep the preferred light level
- Setup button to easily adjust settings such as minimum and maximum dimming range, fade on, startup configuration, and more
- Status LED can be enabled to illuminate when lights are OFF so it is easier to locate the dimmer in the dark
- Single Pole or 3-way when used with a 3-way switch
- Change the color using DSKIT faceplates available in white, ivory, light almond, gray, black, brown and red

Lever Edge Installation Features

- Patented lever terminals for fast, efficient wiring
- Color coded terminals reduce the risk of miswiring
- The only residential device on the market with a ground wire quick termination
- No exposed metal parts for enhanced safety; eliminates need for electrical tape
- Lever doors have “snap” feature to assure connection has been made; audible click confirms lever door is closed
- Lever connectors work with 12 gauge and 14 gauge solid and stranded copper wire
- Wire openings prevent wire insulation from being inserted into the terminals
- Unique tongue and groove alignment feature offers quicker trim out in multi-gang installations
- Test openings for circuit testers
- Fits midway wallplates out of the box with easy break-off fins for compatibility with Decora® and Decora Plus™ standard and screwless wallplates

Patents*

CA2798964 US9431192

US11903105 US8664886
MX321054 US11791573

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 · FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52) 5386- 1797 ·

Visit our Website at: www.leviton.com

© 2026 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/company/about-leviton/locations

© 2026 Leviton Manufacturing Co., Inc.